



AQUA SILICON REMOVER LIQUID

PART#24134M3

DESCRIPTION

Aqua Silicon Remover Liquid (ASRL) is an extremely strong alkaline-concentrate, with specific additives. ASRL is a non-solvent universal cleaning and degreasing product which also removes silicon.

APPLICATION

ASRL can be safely applied to most materials, including aluminum and synthetics.

ADVANTAGES

- Non- flammable, Non-Poisonous, Phosphate free, Non-toxic High bio-degradability
- Meets all EEG Regulations
- Safe for use on ferrous and nonferrous materials, including aluminum, plastics, lacquer and paints.

REPLACEMENT FOR

ASRL is non-solvent degreaser. ASRL is environmentally benign replacement for vapor degreasing solvents, chlorated products and solvent/emulsion cleaners which pose safety, explosion, air, ground and water pollution problems.

CLEANING METHODS

Non Solvent Degreaser can applied by hand.

SPECIFICATIONS

Appearance	Colourless
Specific at 20°C	±1.03
Usage Temperature	10°C up to 40°C
Storage Temperature	Frost Free
Solubility in water	100%
Flash Point	None
Danger Class	None
Ph (Sol. 20ml/l)	>9.5 < 10.5

ECOSTERILE MKTG. PVT. LTD.

Regd. Office : B-2001, Aditya Towers, V. P. Road, Mumbai - 400 004, Maharashtra, INDIA .
Tel. : 91-22-3206 7007 Fax : 91-22-2385 6787
email : info@ecosterile.com Website : www.ecosterile.com

Mfd. By : eOx Productie bv, Le Lulofsdwarsstraat 117, 2521 AZ, The Hague, Netherlands

Disclaimer

ESOSTERILE believes the information contained herein seems to be accurate. However, ECOSTERILE neither gives guarantee nor accepts any liability for the same. In case of litigation, the proper court in Mumbai shall have the Jurisdiction

ECOSTERILE

ENVIRONMENTAL TECHNOLOGIES

DIRECTIONS FOR GENERAL USE:

- ▶ Spray the surface to be cleaned with the diluted product.
- ▶ Allow 10 seconds for the product to work.
- ▶ Remove dirt by sponge or brush.
- ▶ Rinse with water.
- ▶ Mop up.

NOTE: Increased temperature accelerates cleaning time. The selected temperature of the solution may range from 34° F to 194° F. (1°C. to 90° C.). The temperature selection depends on the nature and thickness of the contamination to be removed.

SAFETY	When used un-diluted: For further information see Material Safety Data Sheet
PACKAGE	25 Lltr., 210 Ltr., 1,000 Ltr.
SHELL LIFE	4 years
STORAGE	Do not store under 35°F / 2°C and not above 122°F / 50°C Do not use below 35°F / 2°C.